

GREEN XLR 65 (R-1W)

Tire Size	LI/SS	Type	Rim		Unloaded Inflated Dimension ± 2%				SLR		RC ± 2.5%		RCI	SRI	Maximum Load Capacity (lbs)								Maximum Load Capacity (kgs)								Tire weight	Tire weight	Tread Depth	Tread Depth	Product Code																			
					S.W.		O.D.								Maximum Load Capacity (lbs)								Maximum Load Capacity (kgs)																															
					mm	inch	mm	inch							mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch						mm	inch	mm	inch															
24"	440/65R24	135 D / 138 A8	TL	W 14 L	W13,W15	441	17.4	1182	46.5	538	21.2	3546	139.6	575	mph/psi	9	12	15	17	20	23	29	35	kmph/bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	79	174	45	57	PAR1408																	
															40	2315	2700	3030	3375	3705	3990	4430	4805	65	1050	1225	1375	1530	1680	1810	2010	2180																						
															30	2425	2835	3185	3540	3890	4200	4655	5050	50	1100	1285	1445	1605	1765	1905	2110	2290																						
															25	2505	2920	3285	3650	4015	4320	4795	5205	40	1135	1325	1490	1655	1820	1960	2175	2360																						
															20	2655	3110	3495	3880	4265	4595	5095	5535	30	1205	1410	1585	1760	1935	2085	2310	2510																						
															5 LT	3100	3615	4070	4520	4970	5360	5940	6450	10 LT	1410	1640	1845	2050	2255	2430	2695	2925																						
															5 HT	2655	3110	3495	3880	4265	4595	5095	5535	10 HT	1205	1410	1585	1760	1935	2085	2310	2510																						
															mph/psi	9	12	15	17	20	23	29	35	kmph/bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4																						
															40	2645	3085	3475	3860	4245	4575	5070	5515	65	1200	1400	1575	1750	1925	2075	2300	2500																						
															30	2780	3240	3650	4055	4465	4805	5325	5790	50	1260	1470	1655	1840	2025	2180	2415	2625																						
25	2890	3375	3795	4210	4630	4995	5535	6010	40	1310	1530	1720	1910	2100	2265	2510	2725																																					
20	3045	3550	4000	4445	4885	5270	5830	6340	30	1380	1610	1815	2015	2215	2390	2645	2875																																					
5 LT	3550	4145	4665	5170	5690	6140	6800	7385	10 LT	1610	1880	2115	2345	2580	2785	3085	3350																																					
5 HT	3045	3550	4002	4443	4884	5270	5832	6339	10 HT	1380	1610	1815	2015	2215	2390	2645	2875																																					
24"	480/65R24	140 D / 143 A8	TL	W 15 L	W14L	479	18.9	1234	48.6	562	22.1	3730	146.9	600	mph/psi	9	12	15	17	20	23	29	35	kmph/bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	94	208	50	63	PAR1410																	
															40	2645	3085	3475	3860	4245	4575	5070	5515	65	1200	1400	1575	1750	1925	2075	2300	2500																						
															30	2780	3240	3650	4055	4465	4805	5325	5790	50	1260	1470	1655	1840	2025	2180	2415	2625																						
															25	2890	3375	3795	4210	4630	4995	5535	6010	40	1310	1530	1720	1910	2100	2265	2510	2725																						
															20	3045	3550	4000	4445	4885	5270	5830	6340	30	1380	1610	1815	2015	2215	2390	2645	2875																						
															5 LT	3550	4145	4665	5170	5690	6140	6800	7385	10 LT	1610	1880	2115	2345	2580	2785	3085	3350																						
															5 HT	3045	3550	4002	4443	4884	5270	5832	6339	10 HT	1380	1610	1815	2015	2215	2390	2645	2875																						
															mph/psi	9	12	15	17	20	23	29	35	kmph/bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4																						
															40	2645	3085	3475	3860	4245	4575	5070	5515	65	1200	1400	1575	1750	1925	2075	2300	2500																						
															30	2780	3240	3650	4055	4465	4805	5325	5790	50	1260	1470	1655	1840	2025	2180	2415	2625																						
25	2890	3375	3795	4210	4630	4995	5535	6010	40	1310	1530	1720	1910	2100	2265	2510	2725																																					
20	3045	3550	4000	4445	4885	5270	5830	6340	30	1380	1610	1815	2015	2215	2390	2645	2875																																					
5 LT	3550	4145	4665	5170	5690	6140	6800	7385	10 LT	1610	1880	2115	2345	2580	2785	3085	3350																																					
5 HT	3045	3550	4002	4443	4884	5270	5832	6339	10 HT	1380	1610	1815	2015	2215	2390	2645	2875																																					
24"	540/65R24	146 D / 149 A8	TL	W 16 L	W18L	530	20.9	1312	51.7	590	23.2	3930	154.7	625	mph/psi	9	12	15	17	20	23	29	35	kmph/bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	110	243	50	63	PAR1415																	
															40	3175	3705	4165	4630	5095	5490	6085	6615	65	1440	1680	1890	2100	2310	2490	2760	3000																						
															30	3340	3890	4375	4860	5360	5765	6395	6945	50	1515	1765	1985	2205	2430	2615	2900	3150																						
															25	3440	4015	4520	5015	5525	5955	6595	7165	40	1560	1820	2050	2275	2505	2700	2990	3250																						
															20	3660	4265	4795	5325	5865	6315	7000	7605	30	1660	1935	2175	2415	2660	2865	3175	3450																						
															5 LT	4255	4970	5590	6205	6835	7365	8160	8865	10 LT	1930	2255	2535	2815	3100	3340	3700	4020																						
															5 HT	3660	4265	4795	5325	5865	6315	7000	7605	10 HT	1660	1935	2175	2415	2660	2865	3175	3450																						
															mph/psi	9	12	15	17	20	23	29	35	kmph/bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4																						
															40	3175	3705	4165	4630	5095	5490	6085	6615	65	1440	1680	1890	2100	2310	2490	2760	3000																						
															30	3340	3890	4375	4860	5360	5765	6395	6945	50	1515	1765	1985	2205	2430	2615	2900	3150																						
25	3440	4015	4520	5015	5525	5955	6595	7165	40	1560	1820	2050	2275	2505	2700	2990	3250																																					
20	3660	4265	4795	5325	5865	6315	7000	7605	30	1660	1935	2175	2415	2660	2865	3175	3450																																					
5 LT	4255	4970	5590	6205	6835	7365	8160	8865	10 LT	1930	2255	2535	2815	3100	3340	3700	4020																																					
5 HT	3660	4265	4795	5325	5865	6315	7000	7605	10 HT	1660	1935	2175	2415	2660	2865	3175	3450																																					
28"	440/65R28	138 D / 141 A8	TL	W 14 L	W13	441	17.4	1283	50.5	590	23.2	3878	152.7	39	625	mph/psi	9	12	15	17	20	23	29	35	kmph/bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	89	196	45	57	PAR1413																
																40	2505	2920	3285	3650	4015	4320	4795	5205	65	1135	1325	1490	1655	1820	1960	2175	2360																					
																30	2635	3065	3450	3835	4210	4540	5040	5470	50	1195	1390	1565	1740	1910	2060	2285	2480																					
																25	2735	3185	3585	3980	4375	4720	5225	5680	40	1240	1445	1625	1805	1985	2140	2370	2575																					
																20	2880	3365	3780	4200	4620	4970	5515	5985	30	1305	1525	1715	1905	2095	2255	2500	2715																					
																5 LT	3350	3915	4400	4895	5380	5800	6430	6980	10 LT	1525	1775	1995	2220	2440	2630	2915	3165																					
																5 HT	2880	3365	3780	4200	4620	4970	5515	5985	10 HT	1305	1525	1715	1905	2095	2255	2500	2715																					
																mph/psi	9	12	15	17	20	23	29	35	kmph/bar	0.6	0.8																											

600/65R38	159 D / 162 A8	TL	DW 20 B	W 18 L	611	24.1	1745	68.7	790	31.1	5247	206.6	45	825	5 HT	4455	5195	5845	6485	7135	7695	8520	9260	10 HT	2020	2355	2650	2940	3235	3490	3865	4200	195	430	55	69	PAR1406																											
															mph/psi	9	12	15	17	20	23	29	35	40	46.30	5400	6075	6750	7425	8005	8875	9645						10 HT	2100	2450	2755	3065	3370	3630	4025	4375																		
															40	4630	5400	6075	6750	7425	8005	8875	9645	10 HT	2100	2450	2755	3065	3370	3630	4025	4375						50	2205	2575	2895	3215	3535	3815	4225	4595																		
															25	5025	5865	6595	7330	8065	8690	9635	10470	40	2280	2660	2995	3325	3660	3945	4370	4750						30	2415	2820	3170	3520	3875	4175	4630	5030																		
															20	5325	6210	6990	7765	8540	9205	10205	11090	30	2415	2820	3170	3520	3875	4175	4630	5030						5LT	6205	7240	8140	9045	9950	10725	11890	12925	10 LT	2820	3285	3695	4105	4515	4865	5395	5865									
															5LT	6205	7240	8140	9045	9950	10725	11890	12925	10 LT	2820	3285	3695	4105	4515	4865	5395	5865						5HT	5325	6210	6990	7765	8540	9205	10205	11090	10 HT	2415	2820	3170	3520	3875	4175	4630	5030									
															5HT	5325	6210	6990	7765	8540	9205	10205	11090	10 HT	2415	2820	3170	3520	3875	4175	4630	5030						mph/psi	9	12	15	17	20	23	29	35	40	46.30	5400	6075	6750	7425	8005	8875	9645	10 HT	2100	2450	2755	3065	3370	3630	4025	4375
															40	4630	5400	6075	6750	7425	8005	8875	9645	10 HT	2100	2450	2755	3065	3370	3630	4025	4375						40	5160	6020	6770	7525	8275	8920	9890	10745	65	2340	2730	3070	3415	3755	4045	4485	4875									
															30	5415	6320	7110	7900	8690	9365	10380	11285	50	2455	2865	3225	3585	3940	4250	4710	5120						30	5415	6320	7110	7900	8690	9365	10380	11285	50	2455	2865	3225	3585	3940	4250	4710	5120									
															25	5610	6545	7360	8180	8995	9700	10750	11685	40	2545	2970	3340	3710	4080	4400	4875	5300						25	5610	6545	7360	8180	8995	9700	10750	11685	40	2545	2970	3340	3710	4080	4400	4875	5300									
20	5935	6920	7785	8650	9515	10260	11370	12360	30	2690	3140	3530	3925	4315	4655	5160	5605	20	5935	6920	7785	8650	9515	10260	11370	12360	30	2690	3140	3530	3925	4315	4655	5160	5605																													
5LT	6915	8065	9075	10080	11090	11955	13250	14400	10 LT	3140	3660	4115	4575	5030	5420	6010	6535	5LT	6915	8065	9075	10080	11090	11955	13250	14400	10 LT	3140	3660	4115	4575	5030	5420	6010	6535																													
5HT	5935	6920	7785	8650	9515	10260	11370	12360	10 HT	2690	3140	3530	3925	4315	4655	5160	5605	5HT	5935	6920	7785	8650	9515	10260	11370	12360	10 HT	2690	3140	3530	3925	4315	4655	5160	5605																													
650/65R38	163 D / 166 A8	TL	DW 20 B	46	645	25.4	1811	71.3	830	32.7	5483	215.9	875	875	mph/psi	11.6	14.5	17.4	20.3	23.2	34.8	46.4	52.2	kmph/bar	0.8	1	1.2	1.4	1.6	2.4	3.2	3.6	221	488	59	74	PAR1407																											
															40	6970	7250	7560	7870	8200	9660	11380	12350	65	3160	3290	3430	3570	3720	4380	5160	5600						40	6970	7250	7560	7870	8200	9660	11380	12350	65	3160	3290	3430	3570	3720	4380	5160	5600									
															30	7320	7610	7940	8270	8620	10140	11950	12960	50	3320	3450	3600	3750	3910	4600	5420	5880						30	7320	7610	7940	8270	8620	10140	11950	12960	50	3320	3450	3600	3750	3910	4600	5420	5880									
															25	7630	7940	8290	8620	8970	10580	12460	13510	40	3460	3600	3760	3910	4070	4800	5650	6130						25	7630	7940	8290	8620	8970	10580	12460	13510	40	3460	3600	3760	3910	4070	4800	5650	6130									
															20	8000	8330	8690	9060	9440	11110	13070	14200	30	3630	3780	3940	4110	4280	5040	5930	6440						20	8000	8330	8690	9060	9440	11110	13070	14200	30	3630	3780	3940	4110	4280	5040	5930	6440									
															5LT	9260	9660	10050	10470	10910	12850	15120	16420	10 LT	4200	4380	4560	4750	4950	5830	6860	7450						5LT	9260	9660	10050	10470	10910	12850	15120	16420	10 LT	4200	4380	4560	4750	4950	5830	6860	7450									
															5HT	8000	8330	8690	9060	9440	11110	13070	14200	10 HT	3630	3780	3940	4110	4280	5040	5930	6440						5HT	8000	8330	8690	9060	9440	11110	13070	14200	10 HT	3630	3780	3940	4110	4280	5040	5930	6440									
															SL	16030	16690	17390	18100	18870	22200	26170	28400	SL	7270	7570	7890	8210	8560	10070	11870	12880						SL	16030	16690	17390	18100	18870	22200	26170	28400	SL	7270	7570	7890	8210	8560	10070	11870	12880									
															mph/psi	12	15	17	20	23	35	46	52	kmph/bar	0.8	1	1.2	1.4	1.6	2.4	3.2	3.6						mph/psi	12	15	17	20	23	35	46	52	kmph/bar	0.8	1	1.2	1.4	1.6	2.4	3.2	3.6									
															40	7870	8200	8530	8880	9260	10890	12810	13890	65	3570	3720	3870	4030	4200	4940	5810	6300						40	7870	8200	8530	8880	9260	10890	12810	13890	65	3570	3720	3870	4030	4200	4940	5810	6300									
30	8270	8620	8950	9330	9720	11440	13450	14590	50	3750	3910	4060	4230	4410	5190	6100	6620	30	8270	8620	8950	9330	9720	11440	13450	14590	50	3750	3910	4060	4230	4410	5190	6100	6620																													
25	8620	8970	9350	9720	10140	11930	14020	15210	40	3910	4070	4240	4410	4600	5410	6360	6900	25	8620	8970	9350	9720	10140	11930	14020	15210	40	3910	4070	4240	4410	4600	5410	6360	6900																													
20	9060	9440	9810	10210	10650	12520	14730	15980	30	4110	4280	4450	4630	4830	5680	6680	7250	20	9060	9440	9810	10210	10650	12520	14730	15980	30	4110	4280	4450	4630	4830	5680	6680	7250																													
5LT	10470	10910	11350	11820	12320	14480	17040	18470	10LT	4750	4950	5150	5360	5590	6570	7730	8380	5LT	10470	10910	11350	11820	12320	14480	17040	18470	10LT	4750	4950	5150	5360	5590	6570	7730	8380																													
5HT	9060	9440	9810	10210	10650	12520	14730	15980	10HT	4110	4280	4450	4630	4830	5680	6680	7250	5HT	9060	9440	9810	10210	10650	12520	14730	15980	10HT	4110	4280	4450	4630	4830	5680	6680	7250																													
SL	18100	18870	19620	20440	21300	25040	29450	31940	SL	8210	8560	8900	9270	9660	11360	13360	14490	SL	18100	18870	19620	20440	21300	25040	29450	31940	SL	8210	8560	8900	9270	9660	11360	13360	14490																													
650/65R42	165 D / 168 A8	TL	DW 20 B	645	25.4	1913	75.3	864	34.0	5740	226.0	925	925	mph/psi	9	12	15	17	20	23	29	35	kmph/bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	243	535	59	74	PAR1404																												
														40	5450	6360	7155	7950	8740	9425	10445	11353	65	2470	2885	3245	3605	3965	4275	4740	5150						40	5450	6360	7155	7950	8740	9425	10445	11353	65	2470	2885	3245	3605	3965	4275	4740	5150										
														30	5720	6675	7510	8345	9180	9895	10970	11920	50	2595	3030	3245	3785	4165	4490	4975	5410						30	5720	6675	7510	8345	9180	9895	10970	11920	50	2595	3030	3245	3785	4165	4490	4975	5410										
														25	5925	6915	7780	8640	9505	10245	11360	12345	40	2690	3135	3530	3920	4310	4650	5150	5600						25	5925	6915	7780	8640	9505	10245	11360	12345	40	2690	3135	3530	3920	4310	4650	5150	5600										
														20	6265	7310	8225	9140	10055	10835	12010	13055	30	2845	3315	3730	4145	4560	4915	5450	5925						20	6265	7310	8225	9140	10055	10835	12010	13055																			